AK-15B



SPECIFICATIONS

Model	AK-15B (15" Single Subwoofer)
Power Handling	500W(Cont) / 1000W(Prog) / 2000(Peak)
Frequency Range	30Hz -250KHz
Frequency Response	46Hz -180KHz
Average Sensitivity	100dB(W/m)
Max SPL	128dB(PEAK/1M ±3dB)
Nominal Impedance	8Ω
Nominal Directivity	80º(H) x 70º(V)
Low Frequency Driver	100mm(4") Coil / 380mm(15") woofer
Flying Hardware	20 x M8 points
Connectors	2 x Speakon® NL4MP (1+/1- Input & Link)
Enclosure	CNC made with tongue and grove assembly 15mm MDF
Finish	Touring grade textured black Paint coating
Dimensions	560mm(W)×690mm(H)×600mm(D)
Weight	43.5kg net

<u>Images</u>







Detail

In spite of a small sub-woofer, AK 15B is a 15" single sub-woofer in a system of "Back Road Horn" designed to play shocking and deep low pitched frequency from 4" (100mm) titanium driver and 220mm powerful magnet. It expresses intensive power in a concert hall and club requiring the extreme-level base. Moreover, a 380mm specially-coated unit remains intact without any transformation after a long time and is designed hard to be damaged during the powerful low-pitched sound playing.