

HAMMER™ TK Series

TK-122M

SPECIFICATIONS



Model	TK-122M (12" 2way full range Monitor system)
Power Handling	400W (Cont) / 800W (Prog) / 1600 (Peak)
Frequency Range	42Hz -20KHz
Frequency Response	50Hz -19KHz
Average Sensitivity	101dB(W/m)
Max SPL	127dB(PEAK/1M ±3dB)
Nominal Impedance	8Ω
Nominal Directivity	80°(H) x 60°(V) Horn Rotable
Low Frequency Driver	Titanium Diaphragm 75mm(3") Coil / 310mm(12") woofer
High Frequency Driver	Titanium diaphragm 44mm(1.75") Coil Compression driver
Connectors	2 x Speakon® NL4MP (1+/1- Input & Link)
Enclosure	CNC made with tongue and grove assembly 17mm birch plywood
Finish	Touring grade textured black Paint coating
Dimensions	652mm(W)×342mm(H)×482mm(D)
Weight	22.5kg net

Images



Detail

TK-122M monitor speakers provide solid and deep base sounds that have never been heard from other monitors. Their medium-to-high frequency range applied with 1.75" titanium-compressed driver establishes the best monitoring environment for professional performers with clear and even sound pressure. Also, an enclosure designed with specially-bonded plywood controls unnecessary resonance for stages.