

HAMMER™ TK Series

TK-152M

SPECIFICATIONS

Model	TK-152M (15" 2way full range Monitor system)
Power Handling	450W (Cont) / 900W (Prog) / 1800 (Peak)
Frequency Range	35Hz -20KHz
Frequency Response	45Hz -19KHz
Average Sensitivity	102dB(W/m)
Max SPL	130dB(PEAK/1M ±3dB)
Nominal Impedance	8Ω
Nominal Directivity	70°(H) x 45°(V) Horn Rotable
Low Frequency Driver	Titanium Diaphragm 100mm(4") Coil / 380mm(15") woofer
High Frequency Driver	Titanium diaphragm 75mm(3") Coil Compression driver
Connectors	2 x Speakon® NL4MP (1+/1- Input & Link)
Enclosure	CNC made with tongue and grove assembly 17mm birch plywood
Finish	Touring grade textured black Paint coating
Dimensions	750mm(W)×407mm(H)×522mm(D)
Weight	34.5kg net



Images



Detail

TK-152M monitor speakers provide solid and deep base sounds that have never been heard from other monitors. Their medium-to-high frequency range applied with 3" titanium-compressed driver establishes the best monitoring environment for professional performers with clear and even sound pressure. Also, an enclosure designed with specially-bonded plywood controls unnecessary resonance for stages.